EPV16A

TRUCK MOUNTED BOOM LIFT



- Working height of 15.8m
- Low cost truck mounted articulated boom lift
- Designed to be fitted to most 4.5 tonne and greater GVM vehicles
- Simple and easy to use and maintain
- Versatile, all-steel boom construction




TRUCK MOUNTED BOOM LIFT

EPV16A

DIMENSIONS	EPV16A
Max. working height	15.8m
Max. platform height	13.8m
Horizontal outreach	7.1m
Platform length	0.61m
Platform width	1.07m
Overall width (A)	1.95m
Overall length (B)	6.75m
Stowed height (C)	2.8m

PERFORMANCE	
Platform capacity (SWL)	200kg
Levelling	Mechanical
Turntable rotation	540° non-continuous

POWER	
Power source	Petrol or truck mounted PTO
Hydraulic system	Live hydraulic system



STANDARD FEATURES

- All steel boom and base construction
- Outrigger/boom safety interlock switches
- · Emergency manual bleed down
- Number coded wiring
- Automatic stabilizers
- Hour meter
- · Fail safe hydraulics with check valves
- 5 year sructural warranty

OPTIONS

- AC outlet in platform
- AC motorpower source
- Flashing light on boom
- LV insulation
- Safety harness and lanyard
- Hydraulic outlet in platform
- Airline to platform
- Full deck and access way
- 360° continuous rotation

Examples of suitable trucks:

4.5 tonne GVM or greater required Isuzu NPR300M Wheel base 3.365m (standard units) Hino 300 series 616 Wheel base 3.4m (standard units) NPR 250m 3.36 wheel base 4.5 tonne NPR 300m 3.36 wheel base 6.5 tonne



2/26 Redfern Street, Wetherill Park, NSW 2164, Australia t: +61 1300 900 700 e: sales.au@snorkellifts.com

WORKING ENVELOPE

